



## JIS 16K RF BLIND

Size		Flange			Raised Face		Drilling		Weight
mm	inch	D	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	1/2"	95	12	70	52	1	4	15	0.57
DN 20	3/4"	100	14	75	58	1	4	15	0.75
DN 25	1"	125	14	90	70	1	4	19	1.17
DN 32	1 1/4"	135	16	100	80	2	4	19	1.54
DN 40	1 1/2"	140	16	105	85	2	4	19	1.67
DN 50	2"	155	16	120	100	2	8	19	1.96
DN 65	2 1/2"	175	18	140	120	2	8	19	2.93
DN 80	3"	200	20	160	135	2	8	22	4.26
DN 100	4"	225	22	185	160	2	8	22	6.11
DN 125	5"	270	22	225	195	2	8	25	8.89
DN 150	6"	305	24	260	230	2	12	25	12.32
DN 200	8"	350	26	305	275	2	12	25	18.05
DN 250	10"	430	28	380	345	2	12	29	29.65
DN 300	12"	480	30	430	395	3	16	29	39.22
DN 350	14"	540	34	480	440	3	16	32	56.50
DN 400	16"	605	38	540	495	3	16	35	79.73
DN 450	18"	675	40	605	560	3	20	35	104.73
DN 500	20"	730	42	660	615	3	20	35	129.97
DN 550	22"	795	44	720	670	3	20	38	161.67
DN 600	24"	845	46	770	720	3	24	38	190.76