



## ANSI 150LBS SORF

Size		Flange					Slip On		Raised Face	Drilling		Weight	
mm	inch	D	A	I	T	K	L	M	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	89.0	22.3	15.9	9.5	60.3	4.8	30.2	35.0	1.6	4	15.8	0.40
DN 20	¾"	98.5	27.6	15.9	11.2	69.8	3.1	38.2	42.9	1.6	4	15.8	0.57
DN 25	1"	108.0	34.5	17.5	12.7	79.3	3.2	49.2	50.9	1.6	4	15.8	0.78
DN 32	1¼"	117.5	43.1	20.7	14.3	88.9	4.8	58.8	63.6	1.6	4	15.8	1.05
DN 40	1½"	127.1	49.5	22.3	15.9	98.4	4.8	65.1	73.1	1.6	4	15.8	1.33
DN 50	2"	152.5	61.9	25.5	17.5	120.6	6.4	77.8	92.0	1.6	4	19.0	2.06
DN 65	2½"	177.9	74.6	28.6	20.7	139.7	6.3	90.5	104.8	1.6	4	19.0	3.31
DN 80	3"	190.6	90.6	30.2	22.2	152.4	6.4	108.0	127.1	1.6	4	19.0	3.90
DN 100	4"	228.7	116.0	33.4	22.2	190.5	9.6	135.0	157.2	1.6	8	19.0	5.35
DN 125	5"	254.1	143.7	36.5	22.2	215.9	12.7	163.5	185.8	1.6	8	22.2	6.10
DN 150	6"	279.5	170.6	39.7	23.9	241.3	14.2	192.1	216.0	1.6	8	22.2	7.50
DN 200	8"	343.0	221.4	44.5	27.0	298.4	15.9	246.1	269.9	1.6	8	22.2	12.17
DN 250	10"	406.5	276.3	49.2	28.6	361.9	19.0	304.9	323.9	1.6	12	25.4	16.61
DN 300	12"	482.7	327.1	55.6	30.2	431.8	23.8	365.2	381.1	1.6	12	25.4	26.33
DN 350	14"	533.5	359.1	57.2	33.4	476.2	22.2	400.1	412.8	1.6	12	28.5	34.78
DN 400	16"	597.0	410.4	63.6	34.9	539.7	27.1	457.3	470.0	1.6	16	28.5	45.10
DN 450	18"	635.1	461.7	68.3	38.1	577.8	28.6	504.9	533.5	1.6	16	31.7	49.15
DN 500	20"	698.6	513.0	73.1	41.3	635.0	30.2	558.9	584.3	1.6	20	31.7	62.29
DN 550	22"	749.4	564.3	79.4	44.5	692.1	33.3	609.7	641.4	1.6	20	34.9	72.29
DN 600	24"	812.9	615.9	82.6	46.1	749.3	34.9	663.6	692.2	1.6	20	34.9	87.48
DN 650	26"	869.9	666.7	85.7	49.2	806.4	34.9	723.9	742.9	1.6	24	34.9	104.6
DN 700	28"	927.1	717.6	87.3	50.8	863.6	34.9	781.0	793.7	1.6	28	34.9	119.48
DN 750	30"	984.2	768.3	88.9	52.4	914.4	34.9	831.8	857.2	1.6	28	34.9	135.26