



ANSI 150LBS SORF BSP INTERNAL

Size		Ø GAS	Flange					Slip On		Raised Face		Drilling		Weight
mm	Inch		D	A	I	T	K	L	M	G	F	Bolt No.	H	Kg/Pc
DN 15	½"	½"	89	19.0	15.9	9.5	60.3	4.8	30.2	34.9	1.6	4	15.9	0.41
DN 20	¾"	¾"	98.4	24.5	15.9	11.1	69.8	3.2	38.1	42.9	1.6	4	15.9	0.58
DN 25	1"	1"	108	30.7	17.5	12.7	79.4	3.2	49.2	50.8	1.6	4	15.9	0.81
DN 32	1¼"	1¼"	118	39.5	20.6	14.3	88.9	4.7	58.7	63.5	1.6	4	15.9	1.09
DN 40	1½"	1½"	127	45.2	22.2	15.9	98.4	4.7	65.1	73.0	1.6	4	15.9	1.39
DN 50	2"	2"	152	57.0	25.4	17.4	120.6	6.4	77.8	92.1	1.6	4	19.0	2.15
DN 65	2½"	2½"	178	72.5	28.6	20.6	139.7	6.4	90.5	104.8	1.6	4	19.0	3.36
DN 80	3"	3"	191	85.2	30.2	22.2	152.4	6.4	107.9	127.0	1.6	4	19.0	4.09
DN 100	4"	4"	229	110.5	33.3	22.2	190.5	9.5	134.9	157.2	1.6	8	19.0	5.62