



## DIN 2501 PN 10 RF BLIND

| Size   |      | Flange |    |     | Raised Face |   | Drilling |    | Weight  |
|--------|------|--------|----|-----|-------------|---|----------|----|---------|
| mm     | inch | D      | T  | K   | G           | F | Bolt no. | H  | Kg / Pc |
| DN 15  | ½"   | 95     | 14 | 65  | 45          | 2 | 4        | 14 | 0.64    |
| DN 20  | ¾"   | 105    | 16 | 75  | 58          | 2 | 4        | 14 | 0.93    |
| DN 25  | 1"   | 115    | 16 | 85  | 68          | 2 | 4        | 14 | 1.14    |
| DN 32  | 1¼"  | 140    | 16 | 100 | 78          | 2 | 4        | 18 | 1.66    |
| DN 40  | 1½"  | 150    | 16 | 110 | 88          | 3 | 4        | 18 | 1.85    |
| DN 50  | 2"   | 165    | 18 | 125 | 102         | 3 | 4        | 18 | 2.60    |
| DN 65  | 2½"  | 185    | 18 | 145 | 122         | 3 | 4        | 18 | 3.34    |
| DN 80  | 3"   | 200    | 20 | 160 | 138         | 3 | 8        | 18 | 4.30    |
| DN 100 | 4"   | 220    | 20 | 180 | 158         | 3 | 8        | 18 | 5.29    |
| DN 125 | 5"   | 250    | 22 | 210 | 188         | 3 | 8        | 18 | 7.71    |
| DN 150 | 6"   | 285    | 22 | 240 | 212         | 3 | 8        | 22 | 9.95    |
| DN 200 | 8"   | 340    | 24 | 295 | 268         | 3 | 8        | 22 | 15.88   |
| DN 250 | 10"  | 395    | 26 | 350 | 320         | 3 | 12       | 22 | 23.33   |
| DN 300 | 12"  | 445    | 26 | 400 | 370         | 4 | 12       | 22 | 29.61   |
| DN 350 | 14"  | 505    | 26 | 460 | 430         | 4 | 16       | 22 | 38.31   |
| DN 400 | 16"  | 565    | 26 | 515 | 482         | 4 | 16       | 26 | 47.83   |
| DN 450 | 18"  | 615    | 28 | 565 | 532         | 4 | 20       | 26 | 61.29   |
| DN 500 | 20"  | 670    | 28 | 620 | 585         | 4 | 20       | 26 | 73.27   |
| DN 600 | 24"  | 780    | 28 | 725 | 685         | 5 | 20       | 30 | 98.18   |