



### EN 1092-1 TYPE 01A PN16 REDUCED

Size		Flange				Drilling		Weight
mm	inch	D	A	b	K	nr	d2	Kg / Pc
DN 15	½"	95.0	22.0	10.0	65	4	14	0.48
DN 20	¾"	105.0	27.5	10.0	75	4	14	0.59
DN 25	1"	115.0	34.5	10.0	85	4	14	0.70
DN 32	1¼"	140.0	43.5	10.0	100	4	18	1.02
DN 40	1½"	150.0	49.5	12.0	110	4	18	1.40
DN 50	2"	165.0	61.5	12.0	125	4	18	1.65
DN 65	2½"	185.0	77.5	12.0	145	4	18	2.01
DN 80	3"	200.0	90.5	12.0	160	8	18	2.18
DN 100	4"	220.0	116.0	12.0	180	8	18	2.42
DN 100	4"	220.0	116.0	14.0	180	8	18	2.82
DN 125	5"	250.0	141.5	15.0	210	8	18	3.72
DN 150	6"	285.0	170.5	15.0	240	8	22	4.51
DN 200	8"	340.0	221.5	15.0	295	12	22	5.67
DN 250	10"	405.0	276.5	18.0	355	12	26	8.90
DN 300	12"	460.0	327.5	18.0	410	12	26	10.78
DN 350	14"	520.0	359.0	20.0	470	16	26	16.27
DN 400	16"	580.0	411.0	22.0	525	16	30	20.96
DN 450	18"	640.0	462.0	25.0	585	20	30	27.73
DN 500	20"	715.0	513.5	25.0	650	20	33	35.13
DN 600	24"	840.0	616.5	25.0	770	20	36	46.63