



## JIS 5K RF BLIND

Size		Flange			Raised Face		Drilling		Weight
mm	inch	D	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	80	9	60	48	1	4	12	0.30
DN 20	¾"	85	10	65	52	1	4	12	0.39
DN 25	1"	95	10	75	62	1	4	12	0.50
DN 32	1¼"	115	12	90	72	2	4	15	0.83
DN 40	1½"	120	12	95	78	2	4	15	0.91
DN 50	2"	130	14	105	88	2	4	15	1.29
DN 65	2½"	155	14	130	112	2	4	15	1.88
DN 80	3"	180	14	145	125	2	4	19	2.50
DN 100	4"	200	16	165	145	2	8	19	3.48
DN 125	5"	235	16	200	180	2	8	19	4.94
DN 150	6"	265	18	230	210	2	8	19	7.23
DN 200	8"	320	20	280	255	2	8	23	11.76
DN 250	10"	385	22	345	320	2	12	23	18.86
DN 300	12"	430	22	390	365	3	12	23	23.51
DN 350	14"	480	24	435	405	3	12	25	32.07
DN 400	16"	540	24	495	465	3	16	25	40.69
DN 450	18"	605	24	555	525	3	16	25	51.48
DN 500	20"	655	24	605	575	3	20	25	60.38
DN 550	22"	720	26	665	635	3	20	27	79.34
DN 600	24"	770	26	715	685	3	20	27	91.20