



EN 1092-1 TYPE 05A PN 10

| Size | | Flange | | | Drilling | | Weight |
|--------|------|----------------------|----|-----|----------|----|---------|
| mm | inch | D | T | K | Bolt no. | H | Kg / Pc |
| DN 15 | ½" | USE PN 40 DIMENSIONS | | | | | |
| DN 20 | ¾" | | | | | | |
| DN 25 | 1" | | | | | | |
| DN 32 | 1¼" | | | | | | |
| DN 40 | 1½" | | | | | | |
| DN 50 | 2" | | | | | | |
| DN 65 | 2½" | USE PN 16 DIMENSIONS | | | | | |
| DN 80 | 3" | | | | | | |
| DN 100 | 4" | | | | | | |
| DN 125 | 5" | | | | | | |
| DN 150 | 6" | | | | | | |
| DN 200 | 8" | | | | | | |
| DN 250 | 10" | 395 | 26 | 350 | 12 | 22 | 24.32 |
| DN 300 | 12" | 445 | 26 | 400 | 12 | 22 | 31.13 |
| DN 350 | 14" | 505 | 28 | 460 | 16 | 22 | 43.12 |
| DN 400 | 16" | 565 | 32 | 515 | 16 | 26 | 61.46 |
| DN 450 | 18" | 615 | 36 | 565 | 20 | 26 | 81.77 |
| DN 500 | 20" | 670 | 38 | 620 | 20 | 26 | 103.04 |
| DN 600 | 24" | 780 | 42 | 725 | 20 | 30 | 154.43 |