



## JIS 10K RF BLIND

Size		Flange			Raised Face		Drilling		Weight
mm	inch	D	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	1/2"	95	12	70	52	1	4	15	0.57
DN 20	3/4"	100	14	75	58	1	4	15	0.75
DN 25	1"	125	14	90	70	1	4	19	1.17
DN 32	1 1/4"	135	16	100	80	2	4	19	1.54
DN 40	1 1/2"	140	16	105	85	2	4	19	1.67
DN 50	2"	155	16	120	100	2	4	19	2.08
DN 65	2 1/2"	175	18	140	120	2	4	19	3.07
DN 80	3"	185	18	150	130	2	8	19	3.32
DN 100	4"	210	18	175	155	2	8	19	4.39
DN 125	5"	250	20	210	185	2	8	23	6.93
DN 150	6"	280	22	240	215	2	8	23	9.77
DN 200	8"	330	22	290	265	2	12	23	13.59
DN 250	10"	400	24	355	325	2	12	25	22.11
DN 300	12"	445	24	400	370	3	16	25	27.03
DN 350	14"	490	26	445	415	3	16	25	36.02
DN 400	16"	560	28	510	475	3	16	27	51.00
DN 450	18"	620	30	565	530	3	20	27	67.13
DN 500	20"	675	30	620	585	3	20	27	80.20
DN 550	22"	745	32	680	640	3	20	33	103.50
DN 600	24"	795	32	730	690	3	24	33	117.79