



## UNI 2278/29 PN 16 RF

Size		Flange				Raised Face		Drilling		Weight
mm	inch	D	A	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	95	22.0	12	65	45	2	4	14	0.50
DN 20	¾"	105	27.5	14	75	58	2	4	14	0.73
DN 25	1"	115	34.0	14	85	68	2	4	14	0.88
DN 32	1¼"	140	43.0	16	100	78	2	4	18	1.47
DN 40	1½"	150	49.0	16	110	88	3	4	18	1.61
DN 50	2"	165	61.5	18	125	102	3	4	18	2.17
DN 65	2½"	185	77.0	18	145	122	3	4	18	2.66
DN 80	3"	200	90.0	20	160	138	3	8	18	3.27
DN 100	4"	220	115.5	22	180	158	3	8	18	4.02
DN 125	5"	250	141.0	24	210	188	3	8	18	5.47
DN 150	6"	285	170.0	24	240	212	3	8	22	6.57
DN 200	8"	340	221.0	26	295	268	3	12	22	9.07
DN 250	10"	405	275.0	32	355	320	3	12	25	14.96
DN 300	12"	460	326.0	32	410	378	4	12	25	17.79
DN 350	14"	520	358.0	36	470	438	4	16	25	27.66
DN 400	16"	580	409.0	38	525	490	4	16	30	34.23
DN 450	18"	640	460.2	40	585	550	4	20	30	42.15
DN 500	20"	715	511.0	42	650	610	4	20	33	56.23
DN 600	24"	840	612.6	44	770	725	4	20	36	78.78