



DIN 2634 PN 25 WNRF

Size		Pipe	Flange					Neck			Raised Face		Drilling		Weight		
mm	inch	d1	D	A	T	T-F	K	h1	h2	d3	s	r	F	G	Bolt No.	H	Kg / Pc
DN 15	½"	21.3	95	17.3	16	14	65	38	6	32	2.0	4	2	45	4	14	0.76
DN 20	¾"	26.9	105	22.3	18	16	75	40	6	40	2.3	4	2	58	4	14	1.08
DN 25	1"	33.7	115	28.5	18	16	85	40	6	45	2.6	4	2	68.	4	14	1.29
DN 32	1¼"	42.4	140	37.2	18	16	100	42	6	56	2.6	6	2	78	4	18	1.88
DN 40	1½"	48.3	150	43.1	18	15	110	45	7	64	2.6	6	3	88	4	18	2.10
DN 50	2"	60.3	165	54.5	20	17	125	48	8	75	2.9	6	3	102	4	18	2.80
DN 65	2½"	76.1	185	70.3	22	19	145	52	10	90	2.9	6	3	122	8	18	3.64
DN 80	3"	88.9	200	82.5	24	21	160	58	12	105	3.2	8	3	138	8	18	4.67
DN 100	4"	114.3	235	107.1	24	21	190	65	12	134	3.6	8	3	162	8	22	6.33
DN 125	5"	139.7	270	131.7	26	23	220	68	12	162	4.0	8	3	188	8	26	8.70
DN 150	6"	168.3	300	159.3	28	25	250	75	12	192	4.5	10	3	218	8	26	11.40
DN 200	8"	219.1	360	206.5	30	27	310	80	16	244	6.3	10	3	278	12	26	16.76
DN 250	10"	273.0	425	258.8	32	29	370	88	18	298	7.1	12	3	335	12	30	23.70
DN 300	12"	323.9	485	307.9	34	30	430	92	18	352	8.0	12	4	395	16	30	31.03
DN 350	14"	355.6	555	339.6	38	34	490	100	20	398	8.0	12	4	450	16	33	47.64
DN 400	16"	406.4	620	388.8	40	36	550	110	20	452	8.8	12	4	505	16	36	62.27
DN 450	18"	457.0	670	439.4	42	38	600	110	20	500	8.8	12	4	550	20	36	69.82
DN 500	20"	508.0	730	488.0	44	40	660	125	20	558	10.0	12	4	615	20	36	90.40
DN 600	24"	610.0	845	588.0	46	41	770	125	20	660	11.0	12	5	720	20	39	116.03