



## ANSI 150LBS RF BLIND

Size		Flange			Raised Face		Drilling		Weight
mm	inch	D	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	89.0	11.1	60.3	35.0	1.6	4	15.8	0.43
DN 20	¾"	98.5	12.8	69.8	42.9	1.6	4	15.8	0.62
DN 25	1"	108.0	14.3	79.3	50.9	1.6	4	15.8	0.87
DN 32	1¼"	117.5	15.9	88.9	63.6	1.6	4	15.8	1.17
DN 40	1½"	127.1	17.5	98.4	73.1	1.6	4	15.8	1.55
DN 50	2"	152.5	19.1	120.6	92.0	1.6	4	19.0	2.43
DN 65	2½"	177.9	22.3	139.7	104.8	1.6	4	19.0	3.99
DN 80	3"	190.6	23.8	152.4	127.1	1.6	4	19.0	4.95
DN 100	4"	228.7	23.8	190.5	157.2	1.6	8	19.0	7.10
DN 125	5"	254.1	23.8	215.9	185.8	1.6	8	22.2	8.73
DN 150	6"	279.5	25.5	241.3	216.0	1.6	8	22.2	11.38
DN 200	8"	343.0	28.6	298.4	269.9	1.6	8	22.2	19.77
DN 250	10"	406.5	30.2	361.9	323.9	1.6	12	25.4	28.94
DN 300	12"	482.7	31.8	431.8	381.1	1.6	12	25.4	43.72
DN 350	14"	533.5	35.0	476.2	412.8	1.6	12	28.5	58.43
DN 400	16"	597.0	36.5	539.7	470.0	1.6	16	28.5	76.61
DN 450	18"	635.1	39.7	577.8	533.5	1.6	16	31.7	94.20
DN 500	20"	698.6	42.9	635.0	584.3	1.6	20	31.7	122.89
DN 550	22"	749.4	46.1	692.1	641.4	1.6	20	34.9	151.76
DN 600	24"	812.9	47.7	749.3	692.2	1.6	20	34.9	186.67
DN 650	26"	869.9	50.8	806.4	742.9	1.6	24	34.9	227.39
DN 700	28"	927.1	52.4	863.6	793.7	1.6	28	34.9	266.22
DN 750	30"	984.2	54.0	914.4	857.2	1.6	28	34.9	310.90
DN 800	32"	1060.4	57.1	977.9	908.0	1.6	28	41.3	378.67