



## UNI 6092 PN 10

| Size   |        | Flange |    |     | Drilling |    | Weight  |
|--------|--------|--------|----|-----|----------|----|---------|
| mm     | inch   | D      | T  | K   | Bolt no. | H  | Kg / Pc |
| DN 15  | 1/2"   | 95     | 14 | 65  | 4        | 14 | 0.71    |
| DN 20  | 3/4"   | 105    | 16 | 75  | 4        | 14 | 1.01    |
| DN 25  | 1"     | 115    | 16 | 85  | 4        | 14 | 1.23    |
| DN 32  | 1 1/4" | 140    | 16 | 100 | 4        | 18 | 1.81    |
| DN 40  | 1 1/2" | 150    | 16 | 110 | 4        | 18 | 2.09    |
| DN 50  | 2"     | 165    | 18 | 125 | 4        | 18 | 2.88    |
| DN 65  | 2 1/2" | 185    | 18 | 145 | 4        | 18 | 3.65    |
| DN 80  | 3"     | 200    | 20 | 160 | 4        | 18 | 4.77    |
| DN 100 | 4"     | 220    | 20 | 180 | 8        | 18 | 5.65    |
| DN 125 | 5"     | 250    | 22 | 210 | 8        | 18 | 8.13    |
| DN 150 | 6"     | 285    | 22 | 240 | 8        | 22 | 10.49   |
| DN 200 | 8"     | 340    | 24 | 295 | 8        | 22 | 16.53   |
| DN 250 | 10"    | 395    | 26 | 350 | 12       | 22 | 24.08   |
| DN 300 | 12"    | 445    | 26 | 400 | 12       | 22 | 30.81   |
| DN 350 | 14"    | 505    | 26 | 460 | 16       | 22 | 39.64   |
| DN 400 | 16"    | 565    | 26 | 515 | 16       | 25 | 49.57   |
| DN 450 | 18"    | 615    | 26 | 565 | 20       | 25 | 58.62   |
| DN 500 | 20"    | 670    | 28 | 620 | 20       | 25 | 75.33   |
| DN 600 | 24"    | 780    | 28 | 725 | 20       | 30 | 101.92  |