



EN 1092-1 TYPE 01B PN 40

Size		Flange				Raised Face		Drilling		Weight
mm	inch	D	A	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	95	22.0	14	65	45	2	4	14	0.59
DN 20	¾"	105	27.5	14	75	58	2	4	14	0.73
DN 25	1"	115	34.5	16	85	68	2	4	14	1.01
DN 32	1¼"	140	43.5	18	100	78	2	4	18	1.67
DN 40	1½"	150	49.5	18	110	88	3	4	18	1.83
DN 50	2"	165	61.5	20	125	102	3	4	18	2.44
DN 65	2½"	185	77.5	22	145	122	3	8	18	3.17
DN 80	3"	200	90.5	24	160	138	3	8	18	3.98
DN 100	4"	235	116.0	26	190	162	3	8	22	5.61
DN 125	5"	270	141.5	28	220	188	3	8	26	7.60
DN 150	6"	300	170.5	30	250	218	3	8	26	9.58
DN 200	8"	375	221.5	36	320	285	3	12	30	17.03
DN 250	10"	450	276.5	42	385	345	3	12	33	27.95
DN 300	12"	515	327.5	48	450	410	4	16	33	39.63
DN 350	14"	580	359.5	54	510	465	4	16	36	59.61
DN 400	16"	660	411.0	60	585	535	4	16	39	86.56
DN 450	18"	685	462.0	66	610	560	4	20	39	88.61
DN 500	20"	755	513.5	72	670	615	4	20	42	116.46
DN 600	24"	890	616.5	84	795	735	4	20	48	184.44