



## EN 1092-1 TYPE 01B PN 16

Size		Flange				Raised Face		Drilling		Weight
mm	inch	D	A	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	USE PN 40 DIMENSIONS								
DN 20	¾"									
DN 25	1"									
DN 32	1¼"									
DN 40	1½"									
DN 50	2"	165	61.5	19	125	102	3	4	18	2.31
DN 65	2½"	185	77.5	20	145	122	3	4	18	2.99
DN 80	3"	200	90.5	20	160	138	3	8	18	3.26
DN 100	4"	220	116.0	22	180	158	3	8	18	4.00
DN 125	5"	250	141.5	22	210	188	3	8	18	4.96
DN 150	6"	285	170.5	24	240	212	3	8	22	6.54
DN 200	8"	340	221.5	26	295	268	3	12	22	9.03
DN 250	10"	405	276.5	29	355	320	3	12	26	13.22
DN 300	12"	460	327.5	32	410	378	4	12	26	17.49
DN 350	14"	520	359.0	35	470	438	4	16	26	26.53
DN 400	16"	580	411.0	38	525	490	4	16	30	33.84
DN 450	18"	640	462.0	42	585	550	4	20	30	43.93
DN 500	20"	715	513.5	46	650	610	4	20	33	61.13
DN 600	24"	840	616.5	52	770	725	4	20	36	92.25