



JIS 10K RF

Size		Flange				Raised Face		Drilling		Weight
mm	inch	D	A	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	95	22.2	12	70	52	1	4	15	0.53
DN 20	¾"	100	27.7	14	75	58	1	4	15	0.69
DN 25	1"	125	34.5	14	90	70	1	4	19	1.07
DN 32	1¼"	135	43.2	16	100	80	2	4	19	1.35
DN 40	1½"	140	49.1	16	105	85	2	4	19	1.43
DN 50	2"	155	61.1	16	120	100	2	4	19	1.71
DN 65	2½"	175	77.1	18	140	120	2	4	19	2.41
DN 80	3"	185	90	18	150	130	2	8	19	2.41
DN 100	4"	210	115.4	18	175	155	2	8	19	2.90
DN 125	5"	250	141.2	20	210	185	2	8	23	4.45
DN 150	6"	280	166.6	22	240	215	2	8	23	5.98
DN 200	8"	330	218	22	290	265	2	12	23	7.10
DN 250	10"	400	269.5	24	355	325	2	12	25	11.30
DN 300	12"	445	321	24	400	370	3	16	25	11.69
DN 350	14"	490	358.1	26	445	415	3	16	25	15.34
DN 400	16"	560	409	28	510	475	3	16	27	21.96
DN 450	18"	620	460	30	565	530	3	20	27	27.78
DN 500	20"	675	511	30	620	585	3	20	27	31.63
DN 550	22"	745	562	32	680	640	3	20	33	40.83
DN 600	24"	795	613	32	730	690	3	24	33	43.24